


EMP2-X402

mPCIe to Four RS422 / 485 Module

HIGHLIGHT FEATURES

- PCIe 2.0 compliant. RS-422 / 485 mode configurable by switch. Supports 485HD (Half Duplex) and 485FD (Full Duplex)
- 4800 to 3Mbps serial data rate. 16C550 compatible. 256-byte FIFOs
- Industrial temperature (-40°C to 85°C) operation
- Flexible design with DB-9 connectors and cable
- Termination resistor by jumper setting
- ESD up to 15KV (Electrostatic Discharge) protection circuit to prevent system damage




SPECIFICATIONS

Model Name	EMP2-X402
Module Type	mPCIe to Four RS422 / 485 Module
Form Factor	mPCIe
Function	Serial
Input I/F	PCI Express 2.0 x1
Output I/F	RS-422 / RS-485
Output Port	4
Output Connector	DB-9
Max. Power Consumption	0.33W (3.3V, 100mA)
Dimension (W x L x H/mm)	30 x 50.9 x 8.25
Temperature	Operation : W/T -40°C ~ 85°C (Ta) Storage : -55°C ~ 95°C
Vibration	5G@[7~2000Hz]
Shock	50G@0.5ms
OS Support	Windows : XP (32 bit), 7 (32 / 64 bit), 8 / 8.1 (32 / 64 bit), 10, and above version, WES7, CE7.0 Linux : Kernel 2.6.x and above.
Warranty	3 Years
Notes	Innodisk can provide Linux source for modification.

ORDER INFO.

P/N	Description
EMP2-X402-W1	mPCIe to Four RS422 / 485 Module, Wide Temperature

MECHANICAL DRAWING



PIN DEFINE

RS-485 Half Duplex	RS-485 / 422 Full Duplex	Pin	RS-485 Half Duplex
Port	TX-	1	D-
	TX+	2	D+
	RX+	3	
	RX-	4	
	GND	5	GND
RS-485 / 422 Full Duplex		6	
		7	
		8	
		9	