



# M.2 (P30) 4IE3

## HIGHLIGHT FEATURES


- PCIe Gen 4 x4, NVMe 1.4
- Stable sustained performance
- LDPC ECC engine supported
- 256 bit AES hardware based encryption
- Hybrid write mode with SLC cache enable
- Dynamic thermal management

## SPECIFICATIONS


|                                 |                                                                         |
|---------------------------------|-------------------------------------------------------------------------|
| Model Name                      | M.2 (P30) 4IE3                                                          |
| Flash Type                      | iSLC (3D TLC)                                                           |
| Interface                       | PCIe Gen 4 x4                                                           |
| Form Factor                     | M.2 2230 M Key                                                          |
| Capacity                        | 40GB ~ 160GB                                                            |
| Sequential R / W (MB/sec, max.) | 1,800 / 1,450                                                           |
| P/E Cycle                       | 100,000                                                                 |
| TBW (Max.)                      | 1,978                                                                   |
| Storage Temperature             | -40°C ~ 85°C                                                            |
| Max. Power Consumption          | 3.3W                                                                    |
| Max. Channels                   | 4                                                                       |
| External DRAM Buffer            | N                                                                       |
| H/W Write Protect               | N                                                                       |
| S.M.A.R.T.                      | Y                                                                       |
| AES                             | Y (Optional)                                                            |
| TCG Opal                        | Y (Optional)                                                            |
| Dimension (W x L x H/mm)        | Pure M.2 : 22.0 x 30.0 x 3.5<br>W/T with heat sink : 25.0 x 30.0 x 15.0 |
| Vibration                       | 20G@[7 ~ 2000Hz]                                                        |
| Shock                           | 1500G@0.5ms                                                             |
| MTBF                            | >3 million hours                                                        |
| Warranty                        | 5 Years                                                                 |

DIAGRAM

ST



WT



Note: The appearance of silicone oil seeping out from the inside of the thermal pad is a normal occurrence. Silicone oil is not electrically conductive, so it does not impact the functionality of SSD.

ORDER INFO.

| Operating Temperature | Standard Grade (0°C ~ 70°C) | Industrial Grade (-40°C ~ 85°C) |
|-----------------------|-----------------------------|---------------------------------|
| 40GB                  | DHM23-40GDH1KCBDF           | DHM23-40GDH1KWBDFFH             |
| 80GB                  | DHM23-80GDH1KCBDF           | DHM23-80GDH1KWBDFFH             |
| 160GB                 | DHM23-A60DH1KCBDF           | DHM23-A60DH1KWBDFFH             |

For TCG Opal function, the PN Code 10th ~ 12th will be DH2.

HQ (Taiwan) T +886-2-7703-3000 / E sales@innodisk.com

CN T +86-755-2167-3689 / E sales\_cn@innodisk.com

US T +1-510-770-9301 / E usasales@innodisk.com

EU T +31-40-3045-400 / E eusales@innodisk.com

JP T +81-3-6667-0161 / E jp\_sales@innodisk.com

innodisk